

Enjoy steady water temperature, all year long

Thermeau® offers pool heaters with unmatched quality in terms of performance, durability, reliability and eco-friendliness for optimum comfort.



THERMEAU
POOL HEAT PUMPS

SIGNATURE

Thermeau®: The comfort you deserve

Invest in comfort all year long with Thermeau®'s SIGNATURE residential heat pump. SIGNATURE has been designed specifically for home owners looking for optimal pool and spa temperatures, regardless of the time of day or year, as well as low energy bills and maintenance costs. SIGNATURE is based on our sophisticated and renowned technology that is used in outdoor residential pools across North America. You'll gain peace of mind knowing that you are getting the very best in performance and reliability.

- Best energy-efficiency performance in the industry
- Next-generation North American components
- Laboratory tests to accurately simulate climatic conditions
- Aesthetic yet resistant finish
- Superior soundproofing for greater discretion
- Quick and easy installation
- Accessible, personalized after-sales service

UNSURPASSED ENERGY EFFICIENCY

Tested at an ambient temperature of 80°F (27°C), the Thermeau® pool heater generates a coefficient of performance (COP) of up to 6, meaning it produces up to 6 times more energy than it consumes.



2-year warranty
on labor



7-year warranty
on parts



10-year limited warranty
on our heat exchanger

AHRI CERTIFIED®
www.ahridirectory.org

Heat Pump Pool Heaters
AHRI Standard 1160

AHRI CERTIFICATION

Internationally recognized AHRI certification guarantees a high-performance, energy-efficient product with low environmental impact.


INVEST IN LASTING COMFORT

Proud to design products that exceed the highest industry standards, Thermeau® offers a warranty program that ensures your peace of mind.



Unequaled quality components

S105 - S125 - S140B



Auto-diagnostic electronic thermostat

Accurately controls water temperature to the chosen degree
For energy savings and comfort



Copeland Scroll compressor: The best in the industry

The quietest system on the market
Perfectly suited to all climates and environments
Impressive combination of performance and energy savings
High-quality, low-maintenance components



Triple-action soundproofing

The quietest system available



Lockable panel

Better screen visibility on sunny days
Greater safety and protection from the elements



Profiled fan blade

Exclusive part improves ventilation
Significantly reduces noise



Twisted titanium tube

Increases exchange surface area for better heat transfer
Resistant to pool and spa chemicals



Direct flow union

Drains water caused by condensation
No more wet pavement!

Features

CHOOSE ONE OF OUR MAXIMUM-PERFORMANCE MODELS TO SUIT YOUR NEEDS

Operating specifications	S105	S125	S140B
Volts	230	230	230
Hertz	60	60	60
Phase	1	1	1
Compressor amps	23.2A	24.3A	27.3A
Heat exchanger	Titanium / PVC	Titanium / PVC	Titanium / PVC
Fan motor max. load amps	2.4A	2.4A	2.4A
Fan motor HP	1/3	1/3	1/3
Fan motor speed	825 RPM	825 RPM	825 RPM
Minimum circuit ampacity	40 A	42,5 A	42,5 A
Maximum fuse	60 A	60 A	60 A
Compressor	Copeland Scroll	Copeland Scroll	Copeland Scroll

Test performance levels	S105	S125	S140B
80F amb, 80F water, 80% RH	105,000 BTU/h	121,000 BTU/h	133,000 BTU/h
COP	6	5,5	6
80F amb, 80F water, 63% RH	100,000 BTU/h	116,000 BTU/h	126,000 BTU/h
COP	5,8	5,3	5,8
50F amb, 80F water, 63% RH	70,000 BTU/h	80,000 BTU/h	87,000 BTU/h
COP	4	4	4
Defrost	Air	Air	Air
Refrigerant	R-410A	R-410A	R-410A
Optimal water flow rate (GPM)	40	55	60
Max. water flow rate (GPM)	100	100	100
Max. water temperature	104F	104F	104F
Net weight (lbs)	230	245	265
Shipping weight (lbs)	275	290	310
Dimensions (in.)	L: 39 W: 33 H: 34	L: 39 W: 33 H: 34	L: 39 W: 33 H: 34
Shipping dimensions (in.)	L: 44 W: 35 H: 39	L: 44 W: 35 H: 39	L: 44 W: 35 H: 39

MODELS FOR INGROUND POOLS

Dimensions (ft.)	Surface (ft. ²)	Liters	Gallons US	Good	Better	Best
12 X 24	288	45,460	11,900	S105	S105	S105
14 X 28	392	61,323	16,200	S105	S105	S105
15 X 30	450	70,092	18,500	S105	S105	S105
16 X 32	512	79,871	21,100	S105	S105	S125
18 X 36	648	102,285	26,700	S125	S125	S140B
20 X 40	800	124,918	33,000	S140B	S140B	S140B

* Also available in S65 - S85. Contact us for more information.